

www.info-kod.hr

Kontaktirajte nas za sve dodatne informacije

Info-kod d.o.o. Dinarski put 1b, 10090 Zagreb



www.info-kod.hr

Rješenja koja ubrzavaju i olakšavaju radne i poslovne procese.

U svome smo poslu u potpunosti usredotočeni na korisnikove potrebe i mogućnosti kako bismo iznašli učinkovita, isplativa i dugotrajna rješenja koja će našim korisnicima omogućiti brže i efikasnije obavljanje radnih i poslovnih procesa. Posebnu pažnju pridajemo korisničkoj podršci i raspoloživosti za bilo kakve upite od strane korisnika.

Zadovoljstvo dugogodišnjih korisnika mjerilo je našeg uspjeha.



INFO-KOD prodaja:

tel: 01/3867-444

email: prodaja@info-kod.hr



Looking for a multi-purpose solution for omni-channel retail and Direct Store Delivery? Unitech EP800 is designed to meet those needs!

Unitech moves with the industry

The retail industry is ever-changing and becoming more omni-channel day by day. To move with the fast pace of retail, Unitech has developed the EP800. This POS terminal with payment and printing solutions; is designed to be applicable everywhere and every time.

Proof-of-payment everywhere

The Unitech EP800 is the first Android-based POS Terminal with integrated 30mm thermal printer. With this great functionality, it doesn't matter where the transaction is made, a proof of payment can always be provided. Imagine you are doing a delivery in a tea field somewhere with no possible internet connection for a digital proof. No problem. Do you do a delivery at someone's house in a small remote town? No problem. The EP800 is designed to deal with every eventuality.

A world of possibilities

The EP800 runs on Android which makes adding functionalities easier than before. With a EMV L1/L2 and contactless certification for payment and a chip card and NFC reader,

the basis for efficient payment is already set. Next to this, the EP800 is operated by a strong 1.2 Ghz Quad Core CPU with 2 GB of RAM and 16 GB of ROM.

The EP800 is designed to work in all circumstances, **with a functioning touch screen**, **even when wearing gloves or outside in the rain**. The EP800 can withstand a drop from up to 1.2 meters and operate in freezing cold and blazing heat. In addition to great printing and payment solutions, the EP800 is also supplied with a 1D and 2D CMOS barcode scanner for all-round application in DSD.

Features

- Integrated thermal 30mm printer
- 1D and 2D barcode scanning
- Total weight of only 550 grams
- 7.4V 2800 mAh Li-ION battery with optional 3.8V 5000 mAh
- 5" TFT-LCD touch screen
- EMV L1/L2 and contactless ready
- Integrated chip card, NFC and MSR reader
- Device, roll of paper, psu and comms cable





Version 5 EP800 Specifications

Operation System

CPU 1.2 Ghz Quad core
OS Android 5.1

Memory 2 GB RAM / 16 GB ROM

Card Slot 1X Micro SD

1x SIM 2x SAM

Input Chinese/English and supports handwriting

and soft keyboard

Display

5" TFT-LCD HD (720x1280) color screen Ultra sensitive capacitive touch screen works with gloves and wet fingers

Keys

Front:

User define button, cancel button, confirm button, clear button

Side:

SCAN button (x2), volume switch and

ON/OFF button

Audio

Buzzer and Speaker (Mono)

Communication

Interface USB

WWAN 4G TDD-LTE / FDD-LTE, 3G WLAN WiFi 802.11 b/g/n,
Bluetooth ® Bluetooth ® 4.0,
GPS GPS support

Camera/Photos/Video

5MP camera

Printer

Printer Integrated 2" thermal printer with 30mm paper roll

Paper width: 50 mm; diameter: 30 mm

Barcode scanner

1D and N3680 2D CMOS support

LED illumination for reading barcodes in poor light conditions Reads barcodes from different media (paper, LCD screens)

Card reader

Contactless NFC

ISO 1443 A/B integrated card reader or equivalent such as Mifare, Mifare Plus, Mifare Ultralight, Mifare DESfire card

Additional Support

Chip card, NFC and MSR readers, 2 PSAM slots

Satellite location receiver

Type GNSS
Precision Up to 5m

Power Source

Main battery 7.4V 2800 mAh / 3.8V 5000 mAh LI-ION

battery back, rechargeable

Operation Up to 8 hours of continuous operation with a minimum backlight of 50%, without

printing and depending on application

Enclosure

Dimension 184 mm x 81 mm x 32 mm Weight 550g (including battery)

600g (fully equipped; battery, printer, paper)

Environmental

Operating temp. -0°C to 50°C Storage temp. -20°C to 60°C

Relative humidity 5% ~ 95% (non-condensing)

Drop specification 1.2m

Regulatory Approvals / Certifications

CE & RED certified, EMV L1/L2 & EMV Contactless ready, PCI ready, Paveway ready, Paypass ready

Warranty

Terminal 1 year Battery 3 months

Accessories

Standard Optional Power adaptor, data line, battery Cradle (USB) or (Ethernet/modem) carrying holster/case, wrist strap, stylus

and paper roll.

























