info<mark>kod</mark>

www.info-kod.hr

Kontaktirajte nas za sve dodatne informacije

Info-kod d.o.o. Dinarski put 1b, 10090 Zagreb



www.info-kod.hr

Rješenja koja ubrzavaju i olakšavaju radne i poslovne procese.

U svome smo poslu u potpunosti usredotočeni na korisnikove potrebe i mogućnosti kako bismo iznašli učinkovita, isplativa i dugotrajna rješenja koja će našim korisnicima omogućiti brže i efikasnije obavljanje radnih i poslovnih procesa. Posebnu pažnju pridajemo korisničkoj podršci i raspoloživosti za bilo kakve upite od strane korisnika.

Zadovoljstvo dugogodišnjih korisnika mjerilo je našeg uspjeha.

INFO-KOD prodaja: tel: 01/3867-444 email: prodaja@info-kod.hr

OMNII XT15



ADAPTABILITY GIVES YOU MORE

The Omnii[™] XT15 is uniquely adaptive by design — combining extreme versatility with open innovation to deliver the flexibility you require to adapt as your business needs change. As the next evolution of the Omnii platform, the Omnii XT15 takes the best features of the Omnii XT10 and adds new functionality to create a device that gives mobile workers the greatest access to business applications — anytime, anywhere. With its certified IP67 and IP65 rating, the Omnii XT15 delivers reliable performance and unparalleled adaptability for the most demanding of environments and applications. Find out why Omnii XT15 is the ultimate supply chain handheld solution.



Technology made tough

The Omnii XT15 comes with the option of Windows® CE 6.0 or Windows® Embedded Handheld 6.5 operating systems, both of which integrate seamlessly to automate key processes and boost productivity in real-time. Plus, it is certified IP67 and IP65 so it will work wherever you take it.

Field-upgradeable adaptability

Omnii XT15 is always fit for purpose, so you can configure it the way you want and later bolt on what you need. This allows for future-proof flexibility as hardware can be reconfigured — and not replaced — saving your business up to 30% on lifetime total cost of ownership.

Optimized erognomics

Ergonomics are crucial to ensuring mobile workers are efficient and effective on their jobs. The Omnii XT15 features a balanced construction that is perfectly weighted for comfort, practicality and Natural Task Support. Furthermore, Omnii XT15 is equipped with Kiosk Mode software and transflective touch screens that enable a friendly user interface.

Rugged design for superior reliability and TCO

With a dual IP65 and IP67 sealing rating, workers can spill water on or even drop the device in a puddle of water — or work out in the pouring rain. And even a 6.5 ft./2 m drop to concrete won't impact operation.

Flexible wireless connectivity options

Only Zebra allows you to choose between cellular, Wi-Fi or Narrowband wireless connectivity, bringing you the most wireless options in one device. Support for 802.11a/b/ g/n Wi-Fi provides compatibility with virtually any wireless LAN and plenty of bandwidth to support the modern graphical user interfaces of today's demanding applications. Narrowband support provides robust, affordable and secure wireless connectivity for simple data transactions in expansive outdoor areas such as seaports, rail yards, airports and expansive outdoor yards in manufacturing plants. And support for GSM/GPRS/EDGE and HSPA+ provides fast and reliable connectivity for field workers all around the world.

Real-world practicality

Zebra understands how to make mobile workers more productive in the harshest of environments and we have designed all elements of the Omnii XT15 to reflect that expertise. Built with the Texas Instruments® OMAP3 microprocessor and a designed Custom ASIC architecture, Omnii XT15 delivers industry-leading performance and efficiency with an extended battery life of up to 20 hours. The 3.7 in. VGA color display allows for improved worker visibility and the 95db keypad beeper with vibration feedback is perfect for loud industrial environments.

THE ULTIMATE HANDHELD FOR SUPPLY CHAIN LOGISTICS

VISIT WWW.ZEBRA.COM/OMNIIXT15 OR ACCESS OUR CONTACT DIRECTORY AT WWW.ZEBRA.COM/CONTACT

OMNII XT15 Specs

PHYSICAL CHARACTERISTICS

Dimensions	8.86 in. L x 3.86 in. W x 1.73 in. D (at display); 1.22 in. D (at grip area); 225 mm L x 98 mm W x 44 mm D (at display); 31 mm D (at grip area)
Weight	1.34 lbs./610 g (basic unit with battery)
Keyboard Options	59-key full alpha numeric; 55-key Alpha Numeric; 66-key QWERTY Numeric 36-key Numeric; 36-key Numeric Alpha Modified; 36-key Numeric; Ultra-white backlight
Power	PowerPrecision Lithium ion battery 5000 mAh
Display	3.7" VGA (640 x 480) Transflective Color/Touch Display; 2 Touchs- creen options: High Visibility option, Extreme Duty option
Audio	Integrated microphone and speaker; high volume 95dBA beeper; optional push-to-talk speaker; vibration feedback
Camera (optional)	3 Mega pixel, autofocus, 4X digital zoom, Dual LED flash, Video capable
GPS (optio- nal)	SIRF III GPS Receiver

PERFORMANCE CHARACTERISTICS

СР	U	TI OMAP 3, 800 MHz
	erating stem	Windows® CE 6.0; Windows® Embedded Handheld 6.5
Me	emory	512 MB RAM and 1GB Flash
	ndled plications	Windows CE 6.0: Internet Explorer Embedded; Microsoft Wordpad Windows Embedded Handheld 6.5: Windows® Office Mobile 2010 (includes Word, Excel, PowerPoint, OneNote and SharePoint); Internet Explorer Mobile; Windows Office Outlook Mobile; Windows Media Player Mobile
	rminal Iulation	TekTerm; Wavelink
	ditional ftware	NetMotion Mobility XE VPN; Mobile Control Center (MCC); Kiosk Mode: Total Recall/Tweaklt/Dr. Debug

BAR CODE SCANNER OPTIONS

SE955 1-D Laser; SE965 1-D Laser, SE1224HP 1-D Laser, SE1524ER Extended Range Laser; SE4500 1-D/2-D Standard Range Imager; SE4600 1-D/2-D Extended Range Imager

RFID MODULE OPTIONS

Frequency: 13.56 MHz; Protocols supported: ISO14443 type A, B and
C, ISO 15693; NFC "Reader to Tag" Mode; full Mifare support; Data
encryption: 2 SAM slots; ID1 SAM format; Class A, B and C

ACCESSORIES

Switchable Keyboard, Integrated 1-D, 2-D and AutoRange Scanners, Desktop Docking Station, 6-Slot Spare Battery Charger, Vehicle Cradle, Carry Accessories. For a complete list of accessories, visit:www.zebra.com/omniixt15.

USER ENVIRONMENT

Operating Temp.	-20°C to +50°C / -4°F to +122°F
Storage Temp.	-40°C to +60°C / -40°F to +140°F
Humidity	5% to 95% non-condensing
Sealing	IP67, IP65, IEC 60529
Drop Speci- fication	Multiple 6.5 ft./2 m drops to polished concrete
Integrated Sensors	Motion (accelerometer); digital compass
ESD	+/- 8kV contact, +/- 15kV air discharge

WIRELESS DATA COMMUNICATIONS



Corporate and International Headquarters | Zebra.com/contact

Key, FAST-MSCHAPv2; LEAP; PEAPv0-MSCHAPv2; PEAPv1-GTC; TLS, 64/128 WEP, AESCCMP, TKIP UHF bands: 403 - 470 MHz Narrowhand* Channel Spacing: 12.5 - 25 kHz (optional) RF power: 500 - 1,000mW; Transmission speed: 4.8/9.6 kbps @ 12.5 kHz, 9.6/19.2 kpbs @ 25 kHz WWAN 2.5G GSM/GPRS/EDGE radio, Quad-Band GSM: 850, 900, 1800, 1900 MHz; UMTS 3.8G HSPA+ radio, Five Band UMTS: 800/850, 900, (optional) 1900, 2100 MHz, Quad-Band GSM: 850, 900, 1800, 1900 MHz WPAN Bluetooth® V2.0 + EDR

IEEE 802.11a/b/g/n, CCX v4, 802.1X, WPA / WPA2-Enterprise & Shared

REGULATORY

WLAN

Worldwide Safety, EMC, RF, Laser approvals; CE Mark; E Mark (vehicle cradles); RoHS compliant; WEEE compliant; REACH compliant

WARRANTY

Subject to the terms of Zebra's hardware warranty statement, the Omnii XT15 is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, go to:www.zebra.com/ warranty

SERVICES AND SUPPORT

Service from the Start Primary: A unique service that covers normal wear and tear as well as accidental damage to internal and external components. Includes a collection option with pre-paid ground freight on return shipments.

* HF Module cannot be combined with the following: Omnii XT15f freezer model, Omnii XT15NI model, Long range imager SE4600, Long range laser SE1524ER, Pistol Grip

* Narrowband is only available on CE models. Narrowband cannot be combined with the following: Omnii XT15F Freezer Model, WWAN radio, Long Range Imager SE4600, Long Range Laser SE1524ER, Camera Speaker, Motion sensor (accelerometer)

Ideal For These Applications:

Industries

- Warehousing
- Manufacturing

 Distribution and Logistics

- Utilities
- Transportation and Logistics

©2017 ZIH Corp and/or its affiliates. All rights reserved. Zebra and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. Part number: SS-OMNIIXT15. Printed in USA 04/15.